

Compatibility Chart

for SCHOEPS CMR Microphone Amplifier

June 2019

Legend: Compatible Transmitters
Incompatible Transmitters

Brand	Model	Comments
Audio Ltd.	MiniTX, order no. 900-423 TX 2020 + Evoy TX 2040 EN2 TXP EN2 miniTX3	"AF Level" should be set to "2...9" " - compatible, according to Audio Ltd. compatible, according to Audio Ltd.
Audio Wireless	AWT-1 AWT-2	Needs to be adapted to CMR. For details please contact Audio Wireless Ltd. At www.audiowireless.co.uk . It may necessary to send both, the CMR and your transmitter, to Audio Wireless for modification
Lectrosonics	SM SM +10 UM 200 UM 300B UM 400 UM 400A UM 500 SMB/E01	- - Recommendation: "Aud" < 20 - - - - -
Shure	UHF U1 ULXD1 UHF U1L UHF ULX1	Switch under the clamp should be set to 0dB - - -
Sennheiser	SK 50 SK 5012 SK 5210-II SK 3063-U	Order your CMR with the cable assembled " " maximum SPL reduced by 5dB
Micron	SDR 116 TX 716A	Level should be set to 0...3 "
Wisycm	MTP 22 MTP 30-L	gain switch position should be 3...6 Recommendation: gain = -20 .. +20dB
Not compatible		
AKG	PT 40 Pro PT 4000	
Audio Ltd.	A10	
Sennheiser	SK 5212 SK 9000	
Shure	UHF-R-UR1 Axient Digital	RF interferences
Zaxcom	All models	RF interferences